

STELLAVOX

STELLAVOX PR2 PASSIVE CONTROLLER



A Professional Ultra-Simple Passive Controller

Designed for professional use, the Stellavox PR2 Passive Controller may be used by high quality studios, in portable mobile playback control systems, and in calibration measurement laboratories.

However, thanks to its unique simplicity and intrinsic signal integrity, the Stellavox PR2 Passive Controller is also the best preamplifier to control a pair of Stellavox PW1 or PW2 amplifiers and may be used by the most demanding audiophiles around the world.

Its 5 position input switching and highest quality level adjustment makes it a practical solution for professional monitoring systems or hifi systems of ultimate quality.

Very reasonable in price, but also extremely small in dimensions, the Stellavox PR2 Passive Controller guarantees the lowest possible signal degradation and a much more transparent sound than an active preamplifier could produce. With the high level of sources existing today, the amplification stage is becoming generally unnecessary and induces more problems for no real purpose.

The components used in this circuit are of extremely high quality, most are military grade. The mechanical construction is typical of the notorious "Swiss Made" precision and strength.

SWISS MADE

TECHNICAL DATA

CONTROLS

- Input Switching :
5 inputs.
2 channels.
RCA connectors.
- Level Control.

INPUT IMPEDANCE

- 10 kOhms

OPERATING TEMPERATURE

- Room temperature :
-30 to +40° Celsius
(-22 to +104° Fahrenheit).

SIZE AND WEIGHT

- 15 cm W x 26.5 cm D x 5.5 cm H.
Weight : 0.5 kg net.

FINISH

- Silver anodized metal.

WARRANTY

- 1 year parts and labor.

The logo for Stellavox, featuring the brand name in a stylized, white, serif font against a solid red rectangular background.

MEMBER OF A.I.H.C. GROUP

Worldwide Distribution :
DIGITAL AUDIO TRADING SA
2, Chemin de la Gravière
1227 GENEVA / SWITZERLAND
Phone : +41 22 823 05 65
Fax : +41 22 342 21 20

www.stellavox.com
info@stellavox.com